

Micron Eagle Hydraulics Inc
 1291 N Post Oak Road
 Suite 170
 Houston
 TX 77055
 USA
 Tel: +1 713 812 0720



Micron Eagle Hydraulics Ltd
 Blackburn Industrial Estate
 Kinellar
 Aberdeen
 AB21 0RX
 Scotland UK
 Tel: +44 (0) 1224 790970

SPECIFICATION SHEET SINGLE CAN ATEX FLUID CONDITIONING UNIT I.D. – MEH FC0103



Benefits

- Explosion proof II 3/2 G c IIB T4
- Removes all types of contamination
- Increased operating security
- Increased life of system components

Technical Specification

Max Pressure	0.8 - 5 Bar	
Max Flow	6-240 l/h	
Dirt Capacity	Particles ISO 12103-1 FTD: 1755g	
Max Working Pressure	80°C	
Material Filter Housing	Stainless Steel	
Material Filter Housing	Cellulose/Polymide	
Grade of Cleaning	>0.1 µm	
Safety Valve	Yes, Set @ 6 Bar	
Frame	Trolley	
Hydraulic Connections	Connection In 3/4" BSP;	Connection out 3/8" BSP
Hoses	Can be supplied to suit client requirements	
Dims/Weight	438W x 597H x 418D mm / 24.1kg	

**UNIT CAN BE CONFIGURED TO SUIT CLIENT REQUIREMENTS PRIOR TO MOBILISATION, PLEASE
 CONTACT MICRON EAGLE HYDRAULICS FOR FURTHER INFORMATION AND AVAILABILITY**